

2.54mm HEADER FEMALE

Distributed by Electro-Stock, Inc. sales@electrostock.com
630-682-1542 Fax 630-682-1562 http://www.electrostock.com

- BOTTOM ENTRY
- THREE PCB LAYOUT OPTIONS

SPECIFICATION:

INSULATOR MATERIAL:
GLASS FILLED THERMOPLASTIC
POLYESTER

FLAMMABILITY RATING:
UL 94V-0

INSULATION RESISTANCE:
1000 MEGOHMS MIN. AT 500V DC

OPERATING TEMPERATURE RANGE:
-40° C TO +105° C

DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR 1 MINUTE

CONTACT MATERIAL:
PHOSPHOR BRONZE

CURRENT RATING:
3 AMPS

CONTACT RESISTANCE:
20 MILLIOHMS MAX. AT 1A DC

ORDER INFORMATION:

C348R XX - X - X - X
1 2 3 4 5

- 1: SERIES** C348R BOTTOM ENTRY THROUGH BOARD RECEPTACLE, 2.54mm SPACING
- 2: NUMBER OF CONTACTS**
06 TO 80 CONTACTS
- 3: CONTACT ARRANGEMENT**
D...DUAL ROW
- 4: CONTACT FOOTPRINT DIMENSION**
 - 1...LAYOUT #1 (3.81mm)
 - 2...LAYOUT #2 (5.08mm)
 - 3...LAYOUT #3 (7.62mm)
- 5: CONTACT PLATING**
 - 6...SELECTIVE GOLD FLASH
 - 8...SELECTIVE 15u" GOLD
 - 9...SELECTIVE 30u" GOLD

