

6 5 4 3 2 1

**MATERIAL AND FINISH**  
 Insulator: Polycarbonate, UL-94V-0 rated  
 Contacts: Brass, Tin Plated

**ELECTRICAL SPECIFICATIONS:**  
 Current rating: 10 A/15 A  
 Voltage rating: 250 VAC  
 Insulation resistance: 100 Mohm min. at 500 VDC  
 Dielectric withstanding voltage: 2000 VAC for one minute

**ORDERING CODE:**  
 43R04-1  $\frac{1}{2}$   $\frac{2}{2}$

1) **COLOR**  
 1 = BLACK  
 2 = GRAY

2) **ELECTRICAL CIRCUIT CONFIGURATION**

1 = 10A 250V 70°C  
 15A 250V 70°C  
 2+GROUND

2 = 10A 250V 120°C  
 15A 250V 120°C  
 2+GROUND

**RECOMMENDED  
 PANEL CUTOUT**

REVISIONS  
 CHANGE  
 DATE

Distributed by Electro-Stock, Inc. sales@electrostock.com  
 630-682-1542 Fax 630-682-1562 http://www.electrostock.com

**TOLERANCE**  
 UNLESS OTHERWISE SPECIFIED

X ± 1  
 X.X ± 0.4  
 X.XX ± 0.20

DRAWN BY	GQ	DATE:	10/05/01
CHECK BY	TD	DATE:	10/09/01
APPR BY	PB	DATE:	10/09/01

**Power Dynamics, Inc.**  
 Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: 10A/15A IEC 60320 APPL. OUTLET; SOLDER TERMINALS; SIDE FLANGE, PANEL MOUNT

**43R04-1X2X**

SIZE: A  
 SCALE: NTS

ALL DIMENSIONS FOR REFERENCE ONLY  
 DIMENSIONS ARE IN MILLIMETERS

SHEET 1 of 1  
 REV:

6 5 4 3 2 1