

6

5

4

3

2

1

MATERIAL AND FINISH

Insulator: Nylon 66, black, UL-94V-1 rated  
Contacts: Brass, Tin plated

ELECTRICAL SPECIFICATIONS:

Current rating: 10 A

Voltage rating: 250 VAC

Current rating: 15 A

Voltage rating: 250 VAC

Insulation resistance: 100 Mohm min. at  
500 VDCDielectric withstanding voltage: 2000 VAC  
for one minute

Operating Temperature: 70°C

ORDERING CODE:

PD-43R03-   1  
                  1

1) TERMINAL OPTIONS

1 = .187(4.8)

2 = .250(6.3)

NOTES:

Recommended panel thickness  
0.8mm max. to 3.0mm max.Distributed by Electro-Stock, Inc. sales@electrostock.com  
630-682-1542 Fax 630-682-1562 http://www.electrostock.com

PANEL THICKNESS	A
0.8 - 1.0	25.4
1.0 - 1.2	25.5
1.2 - 1.5	25.6
2.0	25.7
3.0	25.7

TOLERANCE  
UNLESS OTHERWISE SPECIFIEDX ± 1  
X.X ± 0.4  
X.XX ± 0.20

DRAWN BY	GQ	DATE:	10/23/01
CHECK BY	TD	DATE:	10/25/01
APPR BY	PB	DATE:	10/25/01

**Power Dynamics, Inc.**

Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: UNIVERSAL IEC 60320 C13 APPL. OUTLET;  
QC TERMINALS, SNAP-IN

PART #: PD-43R03-X1

SHEET  
1 of 1SIZE: A  
SCALE: NTSALL DIMENSIONS FOR REFERENCE ONLY  
DIMENSIONS ARE IN MILLIMETERS

REV:

REV	DATE	CHANGE	CHK	CHK	APPR

6

5

4

3

2

1