


THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
B	RoHS Compliancy	06-01-06	DP



Distributed by Electro-Stock, Inc. sales@electrostock.com
630-682-1542 Fax 630-682-1562 http://www.electrostock.com

NOTES:

MATERIAL:

MOULDING: NYLON, FLAMMABILITY RATING U.L. 94V-0
CONTACTS: BRASS, NICKEL PLATED
RATING: 10A 250V AC
INSULATION RESISTANCE: >10,000 M OHM
CONTACT RESISTANCE: < 10m OHM
A.C. BREAKDOWN:
POLE-POLE: 4.5kV
POLE-ACCESSIBLE: 4kV
OPERATING TEMPERATURE: -40° C TO +70° C
WITHDRAWL FORCE: 10N (MIN), 50N (MAX)
APPROVALS: UL, CSA, VDE
FOR USE WITH 18 AWG CORDAGE
RoHS COMPLIANT

CONTROLLED

Dim range (mm)	Tolerance +/- (mm)	Qualtek Electronics Corp. PPC DIVISION		
		Part Number:	709-00/00	RoHS Compliant
0-1	0.15	Description: REWIRABLE PLUG ASSEMBLY		
1-6	0.20			
6-18	0.30	UNIT: mm	REV. B	
18-50	0.50		Approved / Date	
50-120	0.70	Drawn / Date	Checked / Date	Approved / Date
120-250	0.90	B.Zhang 04-11-02	04-11-02	JJH / 04-11-02
250-500	1.20			